

2022

NEW RENEGADE® X-RS® WITH COMPETITION PACKAGE

Powerful, lightweight and highly capable race-ready features.



// WHAT'S NEW

- Rotax® 600R E-TEC® engine
- Racing KYB® PRO 40 shock package
- Low profile 90 mm riser bloc
- Standard with 2 sets of LinQ attachment points

// PACKAGE HIGHLIGHTS

- 7.2 in. digital display
- RAS™ X front suspension
- rMotion™ X rear suspension
- Manual starter
- RS running boards
- pDrive™ clutch
- Low windshield with deflectors
- Forward steering post position
- Transparent handguards
- Reinforced rails
- Open toe-hold
- Pilot X skis
- Backlit multifunction handlebar controls

ROTAX® ENGINE

600R E-TEC®

Engine details	Liquid-cooled, two-stroke, eRAVE™
Horsepower	125
Cylinders - Displacement	2 - 599.4 cc
Bore - Stroke	72.3 mm - 73 mm
Carburation	E-TEC® direct injection
Fuel type - Octane	Unleaded - 95
Fuel tank	36 L
Oil tank capacity	3.4 L

POWERTRAIN

Drive clutch	pDrive™ with clickers
Driven clutch	QRS
Drive sprocket pitch	73 mm

DIMENSIONS

Overall vehicle length	3,038 mm
Overall vehicle width	1,217 mm
Overall vehicle height	1,222 mm
Ski stance	1,077 mm
Track (Length x Width x Profile)	137 x 15 x 1.6 in. Cobra

COLOR

Black 

SUSPENSION

Front suspension	RAS™ X
Front shock	KYB PRO 40 R Easy-Adjust
Front suspension travel	265 mm
Rear suspension	rMotion™ X
Center shock	KYB® PRO 40 Easy-Adjust (double-rate springs)
Rear shock	KYB® PRO 40 Easy-Adjust
Rear suspension travel	292 mm

FEATURES

Frame	REV® Gen4
Bodywork	Narrow design
Skis	Pilot™ X
Seating	Trail performance
Handlebar	U-shaped aluminum with J-hooks/ Transparent handguards
Riser block height	90 mm
Starter	Manual
Reverse	RER™
Air radiator	
Brake system	Brembo racing brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	7.2 in. wide digital display
Windshield	360 mm
Runner - Carbide	Round 1/2 - 102 mm
Bumpers (front/rear)	Std/Std

ski-doo

