

2022 TUNDRA™ LT

Great off-trail and deep-snow performance with light-utility capability.



TUNDRA™ LT
600 ACE™ SHOWN

// PACKAGE HIGHLIGHTS

- Rotax® 600 EFI and 600 ACE™ engine with 650W magneto available
- HPG™ rear shock
- 4.5 in. digital display
- LTS telescopic front suspension
- SC™-5U articulating rear suspension with locking mechanism (no tool required)
- Brembo brake with braided stainless-steel brake line
- Heavy-duty rear bumper with hitch
- Air radiator with fan
- Standard electric start
- Deep-snow running boards with large openings
- Standard with two sets of LinQ attachment points
- Pilot™ DS 2 skis
- Low handlebar strap

ROTAX® ENGINE

	600 EFI	600 ACE™
Engine details	Liquid-cooled, two-stroke	Liquid-cooled, four-stroke D.O.H.C., dry sump
Horsepower	85	62
Cylinders - Displacement	2 - 599.4 cc	2 - 600 cc
Bore - Stroke	72.3 mm - 73 mm	73 mm - 69.7 mm
Carburation	EFI	EFI
Fuel type - Octane	Unleaded - 95	Unleaded - 95
Fuel tank	36 L	36 L
Oil tank capacity	3.4 L	2.1 L

POWERTRAIN

Drive clutch	pDrive™ with slider shoes	eDrive™ 2
Driven clutch	QRS	QRS
Drive sprocket pitch	73 mm	73 mm

DIMENSIONS

Overall vehicle length	3,316 mm
Overall vehicle width	994 mm
Overall vehicle height	1,369 mm
Ski stance	813 mm
Track (Length x Width x Profile)	Charger: 154 x 16 x 1.5 in.

COLOR

Neo Yellow / Black

SUSPENSION

Front suspension	LTS
Front shock	Motion Control
Front suspension travel	150 mm
Rear suspension	SC™-5U
Center shock	Motion Control
Rear shock	HPG™
Rear suspension travel	239 mm

FEATURES

Frame	REV® Gen4
Bodywork	Wide design
Skis	Pilot™ DS 2
Seating	Short 2-up
Handlebar	U-shaped aluminum with J-hooks/ Low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	REVER™ (600 EFI) Mechanical (600 ACE™)
Air radiator	Fan
Brake system	Brembo brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital display
Windshield	425 mm
Runner - Carbide	Square 3/8 - 102 mm
Bumpers (front/rear)	Std/Heavy-duty with J-hook type hitch

ski-doo

