

# 2022 MXZ<sup>®</sup> SPORT

Dynamic trail performance and value-oriented features.



**MXZ<sup>®</sup> SPORT  
600 EFI SHOWN**

## // PACKAGE HIGHLIGHTS

- Rotax<sup>®</sup> 600 EFI engine
- 4.5 in. digital display
- RAS<sup>™</sup> 3 front suspension
- SC<sup>™</sup>-5M rear suspension
- Electric starter standard
- Low windshield (360 mm)
- Brembo brake with braided stainless-steel brake line
- U-shaped aluminum handlebar with integrated J-hooks
- Ergo-step side panels
- NEW standard with set of LinQ attachment points

### ROTAX<sup>®</sup> ENGINE

#### 600 EFI

Engine details	Liquid-cooled, two-stroke
Horsepower	85
Cylinders – Displacement	2 – 599.4 cc
Bore – Stroke	72.3 mm – 73 mm
Carburation	EFI
Fuel type – Octane	Unleaded – 95
Fuel tank	36 L
Oil tank capacity	3.4 L

### POWERTRAIN

Drive clutch	pDrive <sup>™</sup>
Driven clutch	QRS
Drive sprocket pitch	73 mm

### DIMENSIONS

Overall vehicle length	2,925 mm
Overall vehicle width	1,217 mm
Overall vehicle height	1,267 mm
Ski stance	1,077 mm
Track (Length x Width x Profile)	RipSaw <sup>®</sup> : 129 x 15 x 1.25 in.

### COLOR

Catalyst Grey / Black 

### SUSPENSION

Front suspension	RAS <sup>™</sup> 3
Front shock	Motion Control
Front suspension travel	220 mm
Rear suspension	SC <sup>™</sup> -5M
Center shock	Motion Control
Rear shock	Motion Control
Rear suspension travel	245 mm

### FEATURES

Frame	REV <sup>®</sup> Gen4
Bodywork	Narrow design
Skis	Pilot <sup>™</sup> 5.7
Seating	Trail compact
Handlebar	U-shaped aluminum with J-hooks
Riser block height	120 mm
Starter	Electric
Reverse	RER <sup>™</sup>
Brake system	Brembo brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital display
Windshield	360 mm
Runner – Carbide	Square 3/8 in. – 102 mm
Bumpers (front/rear)	Std/Std

**ski-doo**

