

2020

RENEGADE® X-RS®

PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC® and 900 ACE™ Turbo engines
- pDrive™ clutch
- RAS™ 3 front suspension
- REV® Gen4 platform with narrow-design (850 E-TEC®) or wide-design (900 ACE™ Turbo) bodywork
- rMotion™ rear suspension
- Forward Adjustable Riser
- KYB® Pro 36 R front shocks and KYB® Pro 40 rear shocks aluminum piggyback with Easy-Adjust compression adjuster (22 clicks)
- Brembo racing brake with braided stainless-steel brake line
- RER™ electronic reverse (850 E-TEC®) / Mechanical reverse (900 ACE™ Turbo)
- RF D.E.S.S.™ key
- Transparent handguards
- Backlit multifunction steering controls
- **7.2-in. wide digital display**
- Optional Adjustment package including rMotion™ Quick Adjust™ system and Pilot™ TS skis or rMotion™ Quick Adjust™ system only
- Open toe-hold
- RS running boards
- Forward steering post position (850 E-TEC®)
- Rack steering system
- 15 x 137 in. track choice: 1.25 in. RipSaw® or Ice Ripper XT or 1.5 in. Ice Ripper XT
- Ergo-Step side panels

RENEGADE®
X-RS® 900 ACE™
TURBO shown



RENEGADE®
X-RS® 850
E-TEC® shown



EXTRA HIGHLIGHTS

900 ACE™ Turbo

- iTC™ Engine mapping modes (Standard, Sport or ECO®)
- Reversible throttle lever (thumb or finger activated)
- Engine oil cooler

ROTAX® ENGINE

	850 E-TEC®	900 ACE™ TURBO
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged
Cylinders	2	3
Displacement	849 cc / 51.9 in. ³	899 cc / 54.9 in. ³
Bore	82 mm / 3.2 in.	74 mm / 2.9 in.
Stroke	80.4 mm / 3.2 in.	69.7 mm / 2.7 in.
Maximum engine speed	7,900 RPM	7,750 RPM
Carburation	E-TEC direct injection with additional booster injectors	EFI
Recommended fuel type	Premium unleaded	Premium unleaded
Minimum octane	91	91
Fuel tank	36 L / 9.5 US gal	36 L / 9.5 US gal
Oil tank capacity	3.4 L / 3.6 qt	3.3 L / 3.5 qt

POWERTRAIN

	850 E-TEC®	900 ACE™ TURBO
Drive clutch type	pDrive™ with clickers	pDrive™
Driven clutch type	QRS	QRS
Engagement	2,900 RPM	2,200 RPM
Small sprocket number of teeth	25	25
Large sprocket number of teeth	45	45
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo racing brake with stainless-steel braided brake line	Brembo racing brake with stainless-steel braided brake line

DRY WEIGHT

226 kg / 497 lb

244 kg / 536 lb

FEATURES

Frame	REV® Gen4	Riser block height	Adjustable-120 mm / 4.7 in.	Mirrors	Optional
Bodywork	Narrow design (850 E-TEC®) Wide design (900 ACE™ Turbo)	Starter	Electric	Windshield	Optional
Skis	Pilot™ 5.7 Pilot™ TS (optional)	Reverse	RER™ (850 E-TEC®) Mechanical (900 ACE™ Turbo)	Runner	Round 7/16
Seating	Trail performance (850 E-TEC®) Trail with storage (900 ACE™ Turbo)	Heated throttle lever/ grips	Standard	Carbide configuration	102 mm / 4 in. at 90°
Handlebar	U-shaped aluminum with J-hooks / Transparent handguards	Gauge	7.2-in. wide digital display	Hitch	Optional

©2019 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™, ® and the BRP logo are trademarks of BRP or its affiliates. Products are distributed in the USA by BRP US Inc. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Printed in Canada.

TWO-STROKE ENGINE



RENEGADE® X-RS® 850 E-TEC® shown



FOUR-STROKE ENGINE



RENEGADE® X-RS® 900 ACE™ TURBO shown



2020 RENEGADE® X-RS®

FEATURE HIGHLIGHTS



Rotax® 850 E-TEC® engine

Next generation of the most advanced direct-injection two-stroke engine technology. Designed for reliability and durability with proven 4-stroke and long-lasting automotive technologies.



Rotax® 900 ACE™ Turbo engine

With a Rotax-built turbocharger specifically designed for the 900 ACE engine, riders get the technology they love with the reliable, powerful performance they demand in one advanced engine package.



KYB® Pro 36 R Easy-Adjust front shocks

Extreme capability, extreme durability shocks with compression and rebound calibration ranges for optimized control in the toughest conditions. Easy Adjust knobs for compression and rebound adjustments.



RS running boards

Designed for aggressive stand-up riding, they are flatter for most of their length, wider and strong. Thicker aluminum sheet, plus front and rear reinforcements to withstand tough landings.



7.2-in. wide digital display

All-digital LCD gauge with customizable display with flatter viewing angle provides riders with preferred info that's easy to see sitting or standing.

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard

ski-doo

