

2021 EXPEDITION SE

// WHAT'S NEW

- Large panoramic 7.8-in. wide LCD color display available
- HPG front and center shocks

// PACKAGE HIGHLIGHTS

- Rotax® 900 ACE™ Turbo engine
- pDrive™ clutch
- REV® Gen4 platform with wide-design bodywork
- 20-in. wide Multi-LinQ plate with 56.7 kg cargo capacity
- SC™-5U articulating rear suspension with locking mechanism on one side (no tool required)
- Air Control Suspension (ACS)
- 20 x 154 track choices: 1.5 in. Silent Cobra WT or Silent Ice Cobra WT
- Air radiator with fan
- RF D.E.S.S.™ key
- Electro-mechanical reverse
- Removable passenger seat and with heated grips
- Ultra large LinQ utility cargo box with 135 L of storage
- Hitch
- High capacity battery
- Forward Adjustable Riser
- Gauge choices: 7.2-in. wide digital display or Large panoramic 7.8-in. wide LCD color display
- 27.5-in. Ultra-high windshield with side deflectors
- Pivoting mirrors
- Deep snow running boards with large openings
- Heated driver's visor power outlet
- Pilot 7.4 skis



EXPEDITION® SE 900 ACE™ TURBO SHOWN

// EXTRA HIGHLIGHTS

900 ACE™ TURBO WITH 650W MAGNETO

- Reversible throttle lever (thumb or finger activated)
- Engine oil cooler
- iTC™ Engine mapping modes (Standard, Sport or ECO)
- High efficiency air radiator with fan

ROTAX® ENGINE

900 ACE™ Turbo

	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged
Engine details	
Cylinders	3
Displacement	899 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7,300 RPM
Carburation	EFI
Recommended fuel type	Unleaded 95
Fuel tank	42 L
Oil tank capacity	3.3 L

POWERTRAIN

Drive clutch type	pDrive™
Driven clutch type	QRS
Engagement	2,000 RPM
Small sprocket number of teeth	Lo = 3.59:1 ratio
Large sprocket number of teeth	Hi = 2.0:1 ratio
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Drive sprocket pitch	73 mm
Brake system	Brembo brake with stainless-steel braided brake line

SUSPENSION

Front suspension	RAS™ 3
Front shock	HPG™
Front suspension travel	210 mm
Rear suspension	SC™-5U
Center shock	HPG™
Rear Shock	ACS (Air Control Suspension)
Rear suspension travel	239 mm

COLOR

Lava Red / Black

DIMENSIONS

Vehicle overall length	3,256 mm
Vehicle overall width	1,200 to 1,240 mm
Vehicle overall height	1,513 mm
Ski stance	975 or 1,020 mm
Track (Length x Width x Profile)	Silent Cobra WT: 154 x 20 x 1.5 in. (3,923 x 500 x 38 mm) Silent Ice Cobra WT: 154 x 20 x 1.5 in. (3,923 x 500 x 38 mm) opt.

FEATURES

Frame	REV® Gen4
Bodywork	Wide design
Skis	Pilot™ 7.4
Seating	2-up modular with underseat storage
Handlebar	U-shaped aluminum with J-hooks / Low grab handle
Riser block height	Adjustable-120 mm
Starter	Electric
Reverse	Electro-mechanic
Heated throttle lever / grips	Standard (driver and passenger)
Gauge type	7.2-in. wide digital display 7.8-in. wide LCD color display (opt.)
Windshield	673 mm with mirrors
Runner	Square 3/8
Carbide configuration	102 mm at 90°
Bumpers (Front/Rear)	Heavy Duty / Hitch

ski-doo



EXPEDITION



EXPEDITION® SE 900 ACE™ TURBO SHOWN

// FEATURE HIGHLIGHTS



Rotax® 900 ACE™ Turbo engine

With a Rotax-built turbocharger specifically designed for the 900 ACE engine, riders get the technology they love with the reliable, powerful performance they demand in one advanced engine package.



Easy Shift transmission (H-L-N) with push-button reverse

Easily shifts with multiple gear ratios. Built for heavy duty reliability with high load resistance and optimal lubrication. Handlebar push-button engages electro-mechanical reverse.



Ultra large LinQ utility cargo box

135 L of lockable, weather resistant storage capacity. Incorporated hatchet and saw holder, plus attachment points for bungees and two 16-in. LinQ positions on top for expandable accessory use.



Multi-LinQ plate

Standard LinQ adaptable storage. Fits 16- and 20-inch-wide LinQ accessories to maximize accessory options. Up to 56.7 kg cargo capacity.



SC™-5U articulating rear suspension

Features settings that maximize deep snow traction in reverse or lock out for towing.