2025

BACKCOUNTRY™ SPORT

For the value-oriented 50-50 rider wanting an advanced platform and modern engine technology.



// PACKAGE HIGHLIGHTS

- Rotax® 600 EFI engine
- 4.5-in. digital display
- RASTM X crossover front suspension with 39 in. ski stance
- cMotion™ rear suspension

- Flectric starter
- Deep snow running boards with large openings
- Glove box with 4 L / 1 US gal of storage
- · Low windshield
- pDrive™ clutch

- Brembo brake
- Standard with 2 sets of LinQ attachment points
- · Pilot DS 2 skis

Bumpers (front/rear)

· Adjustable ski stance

ROTAX ENGINE	600 EFI	
Engine details	Liquid-cooled, two-stroke	
Horsepower*	85	
Cylinders - Displacement	2 - 599.4 cc	
Bore – Stroke (mm)	72.3 x 73	
Fuel System	EFI	
Fuel type – Octane	Regular unleaded - 95	
Fuel tank (L/US gal)	36 / 9.5	
Oil tank capacity (L/qt)	3.4 / 3.6	
POWERTRAIN		
Drive clutch	pDrive™	
Driven clutch	QRS	
Drive sprocket pitch (mm/in.)	73 / 2.86	
DRY WEIGHT		
Dry weight (kg)	203.2	
DIMENSIONS		
Vehicle overall length (mm/in.)	3,174 / 125	
Vehicle overall width (mm/in.)	1,160 / 45.7 (adjustable)	
Vehicle overall height (mm/in.)	1,283 / 50.5	
Ski stance (mm/in.)	1,000 / 39 (adjustable)	
Available tracks (in.)	PowderMax†:	
(Length x width x profile)	146 x 16 x 2.0	

COLOR Neo Yellow SUSPENSION RAS™ X Front suspension Front shock Motion Control Front suspension travel (mm/in.) 220 / 8.7 Rear suspension cMotion™ Center shock Motion Control Rear shock **KYB 36** Rear suspension travel (mm/in.) 239 / 9.4 **FEATURES** REV® Gen4 Platform Headlights Halogen Pilot™ DS 2 Skis Seating Trail narrow compact Handlebar Standard with J-hooks Riser block height (mm/in.) 120 / 4.7 Starter Electric RER™ Reverse Brake system Brembo Heated throttle lever/grips Standard Gauge type 4.5 in. digital Windshield Low Runner (in.) - Carbide (in.) 3/8 square / 4





Std / Std