## 2025

BACKCOUNTRY™ X-RS°

The most aggressive crossover vehicle with snocross attitude and go-anywhere capability.

## // WHAT'S NEW

- Rotax® 850 E-TEC Turbo R engine with Water Injection System available
- 10.25 in. touchscreen display with BRP Connect and built-in GPS



## // PACKAGE HIGHLIGHTS

• REV Gen5 platform

Dry weight (kg)

- Rotax® 850 E-TEC® engine
- High-performance KYB Pro shock package
- RAS  $^{\mbox{\scriptsize M}}$  X crossover front suspension with 39 in. ski stance
- $\cdot$  Glove box with 4 L / 1 US gal of storage
- Backlit multifunction handlebar controls
- pDrive™ clutch with clickers
- Transparent handguards
- Open toe-hold
- Pilot DS 2 skis
- · Adjustable ski stance
- Belt-monitoring system

- cMotion™ X rear suspension with rail reinforcement
- Premium LED headlights
- Precision rack steering system
- · Ice scratchers
- · Adjustable brake lever
- Deep snow running boards with large openings

ROTAX ENGINE	850 E-TEC TURBO R	850 E-TEC	
Engine details	Liquid-cooled, two-stroke, turbocharged, Water Injection System, eRAVE™	Liquid-cooled, two-stroke, eRAVE™	
Horsepower*	180 up to 8,000 ft.	165	
Cylinders - Displacement	2 - 849 cc	2 - 849 cc	
Bore - Stroke (mm)	82 x 80.4	82 x 80.4	
Fuel System	E-TEC® direct injection with additional booster injectors	E-TEC® direct injection with additional booster injectors	
Fuel type – Octane	Regular unleaded - 95	Regular unleaded - 95	
Fuel tank (L/US gal)	36 / 9.5	36 / 9.5	
Oil tank capacity (L/qt)	3.4 / 3.6	3.4 / 3.6	
POWERTRAIN			
Drive clutch Driven clutch	pDrive™ with clickers QRS Vent Plus		
Drive sprocket pitch (mm/in.)	73 / 2.86		

Vehicle overall length (mm/in.)	3,174 / 125 (146 in.)
	3,284 / 129.3 (154 in.)
Vehicle overall width (mm/in.)	1,160 / 45.7 (adjustable, 39 in.)
Vehicle overall height (mm/in.)	1,283 / 50.5
Ski stance (mm/in.)	1,000 / 39 (adjustable)
Available tracks (in.)	PowderMax†:
(Length x width x profile)	146 x 16 x 2.0
	154 x 16 x 2.5

226.8 (146 in.)

JOLUK
-------

Black		
Flare Yellow		
SUSPENSION		
Front suspension	RAS™ X (39 in.)	
Front shock	KYB Pro 36 EA-3	
Front suspension travel (mm/in.)	220 / 8.7 (39 in.)	
Rear suspension	cMotion™ X	
Center shock	KYB Pro 40 EA-3	
Rear shock	KYB Pro 40 EA-3	
Rear suspension travel (mm/in.)	264 / 10.4	

## **FEATURES**

Platform	REV® Gen5
Headlights	Premium high-performance LED
Skis	Pilot™ DS 2 (39 in.)
Seating	Trail narrow
Handlebar	Standard with J-hooks / Transparent handguards
Riser block height (mm/in.)	120 / 4.7
Starter	850 E-TEC: Electric, 850 E-TEC Turbo R: SHOT
Reverse	RER™
Brake system	Brembo with adjustable lever
Heated throttle lever/grips	Standard
Gauge type	"7.2 in. digital 10.25 in. touchscreen (opt., std on Turbo R)"
Windshield	Ultra-low
Runner (in.) - Carbide (in.)	7/16 round / 4
Bumpers (front/rear)	Std / Std





215.5 (146 in.) 218.6 (154 in.)