2025 **EXPEDITION° LE**

A crossover sport-utility vehicle capable of off-trail exploration, on-trail cruises and enjoyable work days.



// PACKAGE HIGHLIGHTS

- Two Rotax® engines available: 900 ACE Turbo, 900 ACE
- Available with 20 in. or 24 in. track options
- Multi-LinQ plate with 125 lb / 56.7 kg cargo capacity
- RAS™ X crossover front suspension with 39 in. ski stance
- SC™-5U articulating rear suspension with locking mechanism (no tool required)
- Air radiator with fan
- Deep snow running boards with large openings
- Removable passenger seat with heated grips
- High passenger backrest
- Hitch
- High capacity battery
- pDrive™ clutch

EXPEDITION LE 900 ACE TURBO SHOWN

- Easy Shift transmission (H-L-N) with electro-mechanical reverse
- · Ultra-high windshield with side deflectors

Windshield

Runner (in.) -

Carbide (in.)

(front/rear)

Bumpers

- Pivoting mirrors
- Pilot 7.4 skis
- Heated driver's visor power outlet
- Low handlebar strap

ROTAX ENGINE	900 ACE TURBO	900 ACE	COLOR
Engine details	Liquid-cooled,	Liquid-cooled,	Black
	four-stroke D.O.H.C.,	four-stroke D.O.H.C.,	
	dry sump,	dry sump	Catalyst Grey
	turbocharged		
Horsepower*	130	95	FEATURES
Cylinders –	3	3	Platform
Displacement	899 cc	899 cc	Headlights
Bore – Stroke (mm)	73 x 69.7	73 x 69.7	Skis
Fuel System	EFI	EFI	Seating
Fuel type – Octane	Regular unleaded - 95	Regular unleaded - 95	Handlebar
Fuel tank (L/US gal)	42 / 11.1	42 / 11.1	
Oil tank capacity (L/qt)	3.3 / 3.5	3.3 / 3.5	
POWERTRAIN			Riser block height (mm/in.)
Drive clutch	pDrive™	pDrive™	Starter
Driven clutch	QRS Vent	QRS	Reverse
Drive sprocket pitch (mm/in.)	73 / 2.86	73 / 2.86	Air radiator
			Brake system
DRY WEIGHT			Heated throttle
Dry weight 20 in. track (kg)	303.5	291.7	lever/grips
Dry weight 24 in. track (kg)	313	301.2	Gauge type

	×	
DIMENSIONS		SUSPENSION
Vehicle overall length (mm/in.)	3,256 / 128.2	Front suspension
		Front shock
Vehicle overall width (mm/in.)	1,200 to 1,240 / 47.7 to 48.8	Front suspension travel (mm/in.)
Vehicle overall height	1,513 / 59.6	Rear suspension
(mm/in.)		 Center shock
Ski stance (mm/in.)	1,000 / 39 (adjustable)	- Rear shock
Available tracks (in.)	Silent Cobra WT: 154 x 20 x 1.5	
		Rear suspension

Available tracks (in.) (Length x width x profile)	Silent Cobra WT: 154 x 20 x 1.5 Silent Cobra SWT: 154 x 24 x 1.5 opt.
(20ingtil x mattil x provide)	

Front suspension	RAS™ X	
Front shock	KYB 36	
Front suspension travel (mm/in.)	220 / 8.7	
Rear suspension	SC™-5U	
Center shock	KYB 36	
Rear shock	KYB 36	
Rear suspension travel (mm/in.)	239 / 9.4	



REV® Gen4

Halogen Pilot™ 7.4 WideTrack 2-up

Standard with J-hooks / Grab handle

145 / 5.7

Electric

Electro-mechanic

Fan Brembo

Standard (driver and

passenger) 4.5 in. digital

Ultra-high with mirrors

3/8 square / 4

Heavy Duty / Hitch



*Observed HP measured on internal dyno test in optimal conditions. ©2024 Bombardier Recreational Products Inc., (BRP), All rights reserved. ™, 🖲 and the BRP logo are trademarks of BRP or its affiliates. Products are distributed in the USA by BRP US Inc. tAll other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.