## 2025

MXZ° SPORT

Dynamic trail performance and value-oriented features.



## // PACKAGE HIGHLIGHTS

- Rotax® 600 EFI engine
- 4.5-in. digital display

**ROTAX ENGINE** 

- RAS™ X front suspension
- SC<sup>™</sup>-5M rear suspension

- Electric starterstandard
- · Low windshield

600 EFI

- U-shaped aluminum handlebar with integrated J-hooks
- Ergo-Step side panels
- 129 in. track lenght available
- Forward steering post position
- · Lower 90 mm riser

KUIAA LIIVIIL	UUU LI I			
Engine details	Liquid-cooled, two-stroke			
Horsepower*	85			
Cylinders - Displacement	2 - 599.4 cc			
Bore - Stroke (mm)	72.3 x 73			
Fuel System	EFI			
Fuel type – Octane	Regular unleaded - 95			
Fuel tank (L/US gal)	36 / 9.5			
Oil tank capacity (L/qt)	3.4 / 3.6			
POWERTRAIN				
Drive clutch	pDrive™			
Driven clutch	QRS			
Drive sprocket pitch (mm/in.)	73 / 2.86			
DRY WEIGHT				
Dry weight (kg)	198.7			
DIMENSIONS				
Vehicle overall length (mm/in.)	2,925 / 115.2 (129 in.)			
Vehicle overall width (mm/in.)	1,211 / 47.8 (adjustable)			
Vehicle overall height (mm/in.)	1,267 / 49.9			
Ski stance (mm/in.)	1,090 / 43 (adjustable)			
Available tracks (in.)	RipSaw <sup>†</sup> :			
(Length x width x profile)	129 x 15 x 1.25			

## COLOR

Neo Yellow

		_	_	_		_	_	_	
S	и	c	D		N	c	ш	n	N
	u	J	г	_	14	J		u	и

SUSPENSION	
Front suspension	RAS™ X
Front shock	Motion Control
Front suspension travel (mm/in.)	235 / 9.3
Rear suspension	SC™-5M
Center shock	Motion Control
Rear shock	KYB 36
Rear suspension travel (mm/in.)	245 / 9.6

## **FEATURES**

Platform	REV® Gen4
Headlights	Halogen
Skis	Pilot™ 5.7
Seating	Trail narrow compact
Handlebar	Standard with J-hooks
Riser block height (mm/in.)	90 / 3.5
Starter	Electric
Reverse	RER™
Brake system	Brembo
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital
Windshield	Low
Runner (in.) – Carbide (in.)	3/8 square / 4
Bumpers (front/rear)	Std / Std



