

2019 EXPEDITION® SE

PACKAGE HIGHLIGHTS

- RAS™ 2 front suspension
- REV-XU™ platform
- SC™-5U articulating rear suspension
- Locking mechanism on one side (no tool required) for articulated suspension
- 500 x 3,923 x 31.8 mm (20 x 154 x 1.25 in.) track
- Air Control Suspension (ACS)
- Console 12V power outlet
- RF D.E.S.S.™ key
- Synchromesh transmission with reverse (2-1-N-R)
- Adjustable, heated passenger grips
- Skid plate, hitch & 680 kg capacity
- WARN winch
- Cargo box (75 L)
- Heavy duty front bumper
- Reversible throttle lever (thumb or finger activated)
- iTC™ Engine mapping modes (Standard, Sport or ECO®)
- Engine oil cooler
- High efficiency air radiator with fan



ROTAX® ENGINE

1200 4-TEC®

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	1,170.7 cc
Bore	91 mm
Stroke	60 mm
Maximum engine speed	7,800 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	45 L
Oil tank capacity	3.5 L

POWERTRAIN

Drive clutch type	eDrive™ 2
Driven clutch type	QRS
Engagement	2,200 RPM
Small sprocket number of teeth	1st gear = 3.23:1 ratio
Large sprocket number of teeth	2nd gear = 1.98:1 ratio
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Hydraulic with braided stainless-steel brake line

DRY WEIGHT

322 kg

FEATURES

Frame	REV-XU™	Starter	Electric	Mirrors	Standard
Skis	Pilot™ DS 2	Reverse	Mechanical	Windshield	580 mm
Seating	2-up modular with underseat storage	Heated throttle lever	Standard	Runner	Square 3/8
Handlebar	Four positions, adjustable tilt steering / Painted steel / J-hooks / Grab handle	Heated grips	Standard (driver and passenger)	Carbide configuration	102 mm at 90°
Riser block height	205 mm	Gauge	Multifunction	Hitch	J-hook type

COLOR

Green / Black

DIMENSIONS

Vehicle overall length	3,370 mm
Vehicle overall width	1,140 to 1,180 mm
Vehicle overall height	1,330 mm
Ski stance	975 or 1,020 mm
Ski overall length	1,049 mm
Track nominal width	500 mm
Track nominal length	3,923 mm
Track profile height	31.8 mm

SUSPENSION

Front suspension	RAS™ 2
Front shock	Motion Control
Front suspension max. travel	210 mm
Rear suspension	SC™-5U
Center shock	Motion Control
Rear shock	ACS (Air Control Suspension)
Rear suspension max. travel	239 mm