

2019 EXPEDITION® SPORT REV® Gen4 **NEW**

PACKAGE HIGHLIGHTS

- Rotax® 900 ACE™ engine with 420W magneto
- **REV® Gen4 platform with wide-design bodywork**
- **pDrive™ clutch**
- SC™-5U articulating rear suspension
- Locking mechanism on one side (no tool required) for articulated suspension
- 406 x 3,923 x 38.1 mm (16 x 154 x 1.5 in.) Charger track
- **RAS™ 3 front suspension**
- Adjustable ski stance
- Brembo brake with braided stainless-steel brake line
- Reversible throttle lever (thumb or finger activated)
- Heated driver's visor power outlet
- Hitch
- RF D.E.S.S.™ key
- iTC™ Engine mapping modes (Standard, Sport or ECO®)
- Air radiator with fan & engine oil cooler
- **2-up seat with removable passenger backrest and handholds**
- Running boards with large openings
- **LinQ™ attach kit (4)**
- Heavy duty rear bumper



ROTAX® ENGINE

900 ACE™

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	899 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7,250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	36 L
Oil tank capacity	3.3 L

POWERTRAIN

Drive clutch type	pDrive™ with slider shoes
Driven clutch type	QRS-MSS
Engagement	2,200 RPM
Small sprocket number of teeth	24
Large sprocket number of teeth	49
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo brake with stainless-steel braided brake line

DRY WEIGHT

254 kg

COLOR

White

DIMENSIONS

Vehicle overall length	3,350 mm
Vehicle overall width	1,140 to 1,180 mm
Vehicle overall height	1,405 mm
Ski stance	975 or 1,020 mm
Ski overall length	1,049 mm
Track nominal width	406 mm
Track nominal length	3,923 mm
Track profile height	38.1 mm Charger

SUSPENSION

Front suspension	RAS™ 3
Front shock	HPG™
Front suspension max. travel	210 mm
Rear suspension	SC™-5U
Center shock	HPG
Rear shock	HPG
Rear suspension max. travel	239 mm

FEATURES

Frame	REV® Gen4	Riser block height	145 mm	Mirrors	Optional
Bodywork	Wide design	Starter	Electric	Windshield	673 mm
Skis	Pilot™ DS 2	Reverse	Mechanical	Runner	Square 3/8
Seating	2-up	Heated throttle lever/ grips	Standard (driver only)	Carbide configuration	102 mm at 90°
Handlebar	U-shaped aluminum with J-hooks	Gauge	Analog with display	Hitch	EU type