

2019 EXPEDITION® XTREME

PACKAGE HIGHLIGHTS

- Rotax® 800R E-TEC® engine
- RAS™ 2 front suspension
- REV-XU™ platform
- SC™-5U articulating rear suspension
- Locking mechanism on one side (no tool required) for articulated suspension
- KYB® Pro 36 aluminum piggyback rear shock with Easy-Adjust compression adjusters (22 clicks)
- HPG™ Plus R front shocks with rebound adjuster
- 500 x 3,923 x 44,5 mm (20 x 154 x 1.75 in.) track
- Adjustable ski stance
- RF D.E.S.S.™ key
- Stiff grab handle on handlebar
- Multifunction digital gauge with engine temperature gauge
- Electric start
- Synchromesh transmission with reverse (2-1-N-R)
- Air radiator with fan
- Rack & Hitch



ROTAX® ENGINE

800R E-TEC®

Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	799.5 cc
Bore	82 mm
Stroke	75.7 mm
Maximum engine speed	7,900 RPM
Carburation	E-TEC direct injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	45 L
Oil tank capacity	3.7 L

POWERTRAIN

Drive clutch type	TRA™ VII
Driven clutch type	QRS
Engagement	3,800 RPM
Small sprocket number of teeth	1st gear = 3.23:1 ratio
Large sprocket number of teeth	2nd gear = 1.98:1 ratio
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo racing brake with stainless-steel braided brake line

DRY WEIGHT

283 kg

FEATURES

Frame	REV-XU™	Starter	Electric	Mirrors	Optional
Skis	Pilot™ DS 2	Reverse	Mechanical	Windshield	360 mm
Seating	1-up modular	Heated throttle lever	Standard	Runner	Square 3/8
Handlebar	Aluminum, tapered with J-hooks / Grab handle	Heated grips	Standard	Carbide configuration	102 mm at 90°
Riser block height	130 mm	Gauge	Multifunction	Hitch	J-hook type

COLOR

Black

DIMENSIONS

Vehicle overall length	3,370 mm
Vehicle overall width	1,140 to 1,180 mm
Vehicle overall height	1,220 mm
Ski stance	975 or 1,020 mm
Ski overall length	1,049 mm
Track nominal width	500 mm
Track nominal length	3,923 mm
Track profile height	44.5 mm

SUSPENSION

Front suspension	RAS™ 2
Front shock	HPG™ Plus R
Front suspension max. travel	210 mm
Rear suspension	SC™-5U
Center shock	HPG™ Plus
Rear shock	KYB® Pro 36 Easy-Adjust
Rear suspension max. travel	239 mm