2017 MXZ® X

PACKAGE HIGHLIGHTS

- RAS™ 2 front suspension
- REV-XS™ platform
- rMotion™ rear suspension
- 15 × 129 × 1.25 in. track choice; RipSaw† or Ice Ripper XT
- KYB† Pro 36 aluminum piggyback rear shock with Easy-Adjust compression adjusters (22 clics)
- HPG™ Plus R aluminum front shocks with no-tool rebound adjuster (22 clics)
- Brembo racing brake with braided stainless-steel brake line
- Backlit multifunction steering controls
- Transparent handguards
- REV-XP™ X seat with 5L / 1.3 us gal of storage
- Glove box with 4 L / 1 US gal of storage
- RF D.E.S.S.™ key
- Optional Adjustment package including rMotion™ Quick Adjust™ system and P lot™ TS skis

EXTRA HIGHLIGHTS

- Engine o l cooler
- iTC™ Engine mapping modes (Standard, Sport or ECO)
- Reversible throttle lever (thumb or finger activated)
- Learning-Key included
- Mechanical reverse
- Extended heat exchanger for better cooling capacity

600 H.O. E-TEC shown

ROTAX® ENGINE

	600 H.O. E-TEC®	1200 4-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3
Displacement	594.4 cc / 36.3 in.³	1170.7 cc / 71.4 in.³
Bore	72 mm / 2.8 in.	91 mm / 3.6 in.
Stroke	73 mm / 2.9 in.	60 mm / 2.4 in.
Maximum engine speed	8100 RPM	7800 RPM
Carburation	Electronic Direct Injection	EFI
Recommended fuel type	Premium unleaded	Regular unleaded
Minimum octane	91	87
Fuel tank	40 liters / 10.6 gallons	40 liters / 10.6 gallons
Oil tank capacity	3.7 liters / 3.9 quarts	3.5 liters / 3.7 quarts

POWERTRAIN

Drive clutch type	TRA™ III	eDrive™ 2
Driven clutch type	QRS	QRS
Engagement	3400 RPM	2200 RPM
Small sprocket number of teeth	23	24
Large sprocket number of teeth	45	43
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo racing brake with stainless-steel braided brake line	Brembo racing brake with stainless-steel braided brake line

DRY WEIGHT

211 kg / 465 lb	234 kg / 515 lb

COLOUR

Sunburst Yellow
Black

DIMENSIONS

Vehicle overall length	3010 mm / 118.5 in.
Vehicle overall width	1217 mm / 47.9 in.
Vehicle overall height	1130 mm / 44.5 in.
Ski stance	1077 mm / 42.4 in.
Ski overall length	1066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3269 mm / 129 in.
Track profile height	31.8 mm / 1.25 in. RipSaw† or 31.8 mm / 1.25 in. Ice Ripper XT

SUSPENSION

Front suspension	RAS™ 2
Front shock	HPG™ Plus R
Front suspension max. travel	208 mm / 8.2 in.
Rear suspension	rMotion™
Center shock	HPG™ Plus
Rear shock	KYB† Pro 36 EA
Rear suspension max. travel	272 mm / 10.7 in.
rMotion Quick Adjust System	Optional

FEATURES

Frame	REV-XS™	Reverse	RER™ (600 H.O) Mechanical (1200 4-TEC)	Mirrors	Optional
Skis	P lot™ 5.7 P lot™ TS (Optional)	Heated throttle lever	Standard	Windshield	285 mm / 12 in.
Seating	REV-XP™ X with storage	Heated grips	Standard	Runner	Square 5/16
Handlebar	Straight aluminum with J-hooks	Gauge	Multifunction	Carbide configuration	102 mm / 4 in. at 90°
Riser block height	130 mm / 5.1 in.	Electric start	Standard	Hitch	Optional

1200 4-TEC shown

FEATURE HIGHLIGHTS

1200 4-TEC shown

RAS™ 2 Front suspension

A taller ski spindle, refined geometry and lighter components sharpen the sled's already precise handling, especially in extreme conditions.

rMotion™ with 15 x 129 x 1.25 in. track

129 inch (327 cm) length adds even more performance to the acclaimed rMotion™ rear suspension, without sacrificing any cornering ability. Riders get more traction, better braking and more bump filtration without sacrificing the precise handling and cornering MXZ sleds are known for.

Adjustable Pilot™ TS Skis (option)

Radical new concept enables the rider to literally dial in the amount of ski bite for conditions and riding style in seconds. A knob adjacent to the ski leg raises or lowers the ski runner – fully extended for a very aggressive bite. There are 20 settings over a .5 in. / 12.5 mm range.

LinQ™ cargo system (option)

Our cargo attachment system is the hassle-free way to connect cargo bags or a fuel caddy to your sled in seconds.

Multifunction gauge with LCD screen

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard

©2016 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™,® and the BRP logo are trademarks of BRP or its affiliates. Products are distributed in the USA by BRP US Inc. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Printed in Canada.

ski-doo BRP